



GE  
Security

## Product Data Sheet

### RF572NSTI4

Smoke Sensor RF 433 MHz



#### Standard Features

- Learn-Mode Technology
- Sensor tamper switch
- Built-in sounder for alarm
- Visual status LED
- CleanMe(c) signal
- Maintenance alert
- Low battery signal
- Replaceable optical chamber
- Integrated fixed 57.2C temperature and rate-of-rise heat detector

# RF572NSTI4

Smoke Sensor RF 433 MHz

## Specifications

<b>Battery type</b>	2 x 3 V Lithium
<b>Battery lifetime (typical)</b>	3 years
<b>Operating frequency</b>	433 MHz
<b>Open-air range</b>	150 m
<b>Operating range</b>	4° C to 38° C
<b>Storage Temperature</b>	-34° C to 60° C
<b>Humidity</b>	90% non-condensing
<b>Rate-of-rise</b>	8.3° C/min > 41° C
<b>Fixed</b>	57.2° C +/-3° C
<b>Dimensions</b>	
Detector	139 x 58mm
<b>Dimensions</b>	
Base	124 x 10mm

## Ordering Information

Part No.	Description
RF572NSTI4	Smoke Sensor RF 433 MHz
DL123A	3 V Lithium battery Duracell DL123A (unit)
SC008	Aerosol test Spray for Smoke detectors



[www.gesecurity.net](http://www.gesecurity.net)